



**HIKVISION**  
accessories

## Estación exterior modular para videoportero ip con 12 botones

**DS-KD-K12**

### AMBIENTE

Temperatura de funcionamiento	<b>-30 °C ~ 55 °C</b>
Grado de protección	<b>IP65</b>
Uso	<b>Exterior</b>
Humedad máxima	<b>90%</b>

### MATERIAL Y DIMENSIONES

Instalación	<b>Superficie / empotrar</b>
Dimensiones	<b>98.2 x 100.2 x 33.7 mm</b>
Peso neto	<b>190 g</b>
Peso con embalaje	<b>360 g</b>

### SISTEMA

Procesador	<b>Embedded Processor</b>
Sistema operativo	<b>Embedded LINUX</b>

### APERTURA

Elementos de llamada	<b>Botones sencillos</b>
----------------------	--------------------------

### ALIMENTACIÓN Y CONSUMO

Modo alimentación	<b>Alimentado a través del DS-KD8003-IME1</b>
Consumo (w)	<b>2W</b>

### INFORMACIÓN GENERAL

Tipo	<b>Estación exterior modular para videoportero ip con 12 botones</b>
------	----------------------------------------------------------------------

### ENTRADAS/SALIDAS

RS485	<b>1</b>
-------	----------



Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.  
Address: No.555 Quannan Road, Binjiang District, Hangzhou 310052, China  
Importer: Hikvision Europe B.V.  
Address: Dirk Steenlaan 5, 2112 PX Hoofddorp, The Netherlands

**HIKVISION**  
Multi-NameTag Module  
Model: DS-KD-K12  
IP: 12V=0.5A  
OP: 12V=0.5A  
SN: FK2308167  
SE2014 Made in China  
CAN ICES 3/A(MWB-3/A)  
CE  
Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.  
Address: No.555 Quannan Road, Binjiang District, Hangzhou 310052, China

RS485 In | RS485 Out