

UTEPO

PoE injector

UTP7201GE-PSE30



POE

Power Pin Assignment	Pair : 1 / 2 (+) , 3 / 6 (-)
Ausgangswelligkeit	< 5 %
Power output	DC 54.5V / 30V
Input port	RJ45
PoE output	RJ45

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%
Lightning protection	6KV

PROTECTION AGAINST RAYS

ESD contact to electronic board	8KV
Protección contra sobretensiones	IEC61000-4-2
Protección sobretensiones línea a tierra	PoE : 1KV / Ethernet : 2KV
Protección sobretensiones línea a línea	PoE: 2KV / Ethernet 6KV

NET STANDARD

IEEE802,3af	Sí
IEEE802,3at	Sí

MATERIAL AND DIMENSIONS

Dimensions	160 x 64 x 40 mm
Material	ABS plastic
Net weight	200 g
Weight with packaging	400 g

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V

ETHERNET PORTS

Transmission distance	Hasta 100 m
10 / 100 / 1000	1

SPECS AND FEATURES

Type	Injector PoE
------	--------------

