

HIKVISION®



Ip recorder of 8 channel and 12 mpx resolution with 8 PoE ports

DS-7608NI-I2-8P

NETWORK FEATURES

PoE ports	8
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	32
Mobile devices	Android / IOS (Apple)
Type PoE	802.3at / af
PoE consumption	120W
Software	IVMS
App	Hik-Connect

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	80Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
ANR (Redundant Recording in SD)	Sí
Output bandwidth	256Mbps

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Consumption (w)	15W

STORAGE

Number of supported hard drives	2
Maximum hard disk size (Unit)	8 TB
Type HDD	3,5 SATA"

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Maximum humidity	90%

VIDEO

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
Resolución VGA	1080P

INPUTS/OUTPUTS

Alarm input	4
USB 2.0	1
USB 3.0	1
Alarm output	1

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

SPECS AND FEATURES

Technology	IP
Serie	PRO

MATERIAL AND DIMENSIONS

Dimensions	385 x 315 x 52 mm
Net weight	3000 g

INTELLIGENT VIDEO SYSTEM

POS	Yes
VCA	Sí

IP Channels

8

Resolution IP cameras

12 Megapíxeles

