



Bullet 4 in 1 (cvi, tvi, ahd and analog) camera of 2 megapixels and varifocal lens

**HWT-B320-VF**

## VIDEO (CAMERAS)

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| Resolución vídeo  | <b>2 Megapixels</b>                                    |
| BLC               | <b>Yes</b>                                             |
| AGC               | <b>Yes</b>                                             |
| WDR               | <b>DWDR</b>                                            |
| Images per second | <b>25fps</b>                                           |
| Video output      | <b>1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS</b> |
| Day / night mode  | <b>Automatic</b>                                       |
| OSD menu          | <b>Yes</b>                                             |
| Mirror            | <b>On / Off</b>                                        |

## DISTANCE DORI

|                         |              |
|-------------------------|--------------|
| Detect (Open lens)      | <b>34 m</b>  |
| Detect (Closed Lens)    | <b>125 m</b> |
| Observe (Open lens)     | <b>14 m</b>  |
| Observe (Closed lens)   | <b>52 m</b>  |
| Recognize (Open lens)   | <b>7 m</b>   |
| Recognize (Closed lens) | <b>26 m</b>  |
| Identify (Open lens)    | <b>3 m</b>   |
| Identify (Closed lens)  | <b>13 m</b>  |

## POWER CONSUMPTION

|                 |              |
|-----------------|--------------|
| Power mode      | <b>DC</b>    |
| Voltage         | <b>12V</b>   |
| Consumption (w) | <b>4.8W</b>  |
| Amperage        | <b>400mA</b> |

## SPECS AND FEATURES

|                |                                          |
|----------------|------------------------------------------|
| Technology     | <b>4 IN 1 (CVI, TVI, AHD and analog)</b> |
| Type of camera | <b>Bullet</b>                            |
| Serie          | <b>HiWatch</b>                           |

## MATERIAL AND DIMENSIONS

|            |                               |
|------------|-------------------------------|
| Dimensions | <b>256.4 x 83.3 x 78.2 mm</b> |
| Material   | <b>Metal and plastic</b>      |
| Net weight | <b>600 g</b>                  |

## IMAGE

|                          |                                  |
|--------------------------|----------------------------------|
| Sensor                   | <b>CMOS ®</b>                    |
| Resolución sensor        | <b>1920 x 1080</b>               |
| Electronic shutter speed | <b>1/25s (1/30)s ~ 1/50,000s</b> |
| Minimum lighting         | <b>0.01Lux</b>                   |

## NIGHT VISION

|                         |             |
|-------------------------|-------------|
| Night vision distance   | <b>40 m</b> |
| Tipo de visión nocturna | <b>IR</b>   |
| Smart IR                | <b>Yes</b>  |
| EXIR                    | <b>Yes</b>  |

## AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-40 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP66</b>           |
| Use                   | <b>Indoor-outdoor</b> |
| Maximum humidity      | <b>90%</b>            |

## LENS

|                |                       |
|----------------|-----------------------|
| Lens Type      | <b>Varifocal</b>      |
| Focal distance | <b>2.8 mm ~ 12 mm</b> |
| Angle of View  | <b>111.5° ~ 33.4°</b> |

## AXES

|        |               |
|--------|---------------|
| Motion | <b>2-Axis</b> |
|--------|---------------|

