

P ▲ R ▲ D O X

Hybrid panel

MG5050



COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
RTC	Sí
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Communication with CRA	Sí
Mobile Network	GPRS / GSM (with PCS module)

ZONES

Maximum number of zones	32
Keyboard areas	15
Wired on-board zones	5
ATZ (Double zones)	Sí

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD
Call notification	Yes, with IP or PCS module (GPRS)

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

CERTIFICATION

Grade	2
Normative	EN50131

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Sí, 12V 4 ~ 7 Ah

PROGRAMMABLE OUTPUTS

Board	4
Maximum of PGMs	16
siren	Sí
Telephone line	Sí

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	256

MATERIAL AND DIMENSIONS

Dimensions	190 x 102 mm
Net weight	20 g

GENERAL INFORMATION

Type of Central	Hybrid
-----------------	---------------

