

P ▲ R ▲ D O X

Hybrid panel

MG5000



COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
RTC	Sí
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires
Communication with CRA	Sí
Mobile Network	GPRS / GSM (with PCS module)

ZONES

Maximum number of zones	32
Keyboard areas	15
Wired on-board zones	2 (4 with ATZ)
ATZ (Double zones)	Sí

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD
Call notification	Yes, with IP or PCS module (GPRS)

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

GENERAL INFORMATION

Type of Central	Hybrid
-----------------	---------------

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	1200mA
Battery support	Sí, 12V 4 ~ 7 Ah

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	256
Maximum users	32

PROGRAMMABLE OUTPUTS

Maximum of PGMs	16
siren	Sí
Telephone line	Sí

MATERIAL AND DIMENSIONS

Dimensions	140 x 104 mm
Net weight	20 g

