



HIKVISION
intrusion

Wired volumetric detector

KX15DQ

DETECTION

Detector type	Wired
Detection distance	15 m
Angle detection	85°
Installation height	1.8 m ~ 2.4 m
Detection method	Infrared
Detection speed	0,3 m/s ~ 3 m/s
Detection zones	60
Blue Wave technology (infrared noise improvement)	Si
Detection technology	Volumetric

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Relay output type	DC
Relay voltage output	60V
Relay Amperage output	50mA

ESPECIFICACIONES TÉCNICAS

Compatibility	Wired centrals
Contact resistance	ess than 10 ohms
Tamper	Si
EOL resistors (end of line)	Si

LENS

Lens Type	Ultraviolet light filter
-----------	---------------------------------

SENSOR

Type of sensor	Pyro-electric
Sensitivity adjustment	Si
High sensitivity	Si
Low sensitivity	Si
Digital temperature compensation	Si

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	117 x 69 x 50 mm
Material	ABS plastic
Net weight	125 g

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

AMBIENT

Operating temperature	-40 °C ~ 80 °C
-----------------------	-----------------------

