



## P ▲ R ▲ D O X

### Wired keypad

#### K641+

#### CHARACTERISTICS (KEYBORDS)

|                   |                       |
|-------------------|-----------------------|
| Connection        | <b>Wired</b>          |
| Screen            | <b>Sí</b>             |
| Screen type       | <b>LCD</b>            |
| Compatibility     | <b>EVO192 / EVOHD</b> |
| Language          | <b>Multilanguage</b>  |
| Panic alarms      | <b>3</b>              |
| Communication way | <b>Bus 4 hilos</b>    |
| Zonas             | <b>32</b>             |
| Action buttons    | <b>14</b>             |
| Keys language     | <b>Spanish</b>        |

#### FUNCTIONS (KEYBOARDS)

|                           |           |
|---------------------------|-----------|
| PGM outputs               | <b>1</b>  |
| Armed function            | <b>Sí</b> |
| Unarmed function          | <b>Sí</b> |
| Brightness adjustment     | <b>Sí</b> |
| Contrast adjustment       | <b>Sí</b> |
| Scroll speed adjustment   | <b>Sí</b> |
| Supported firmware update | <b>Sí</b> |

#### MATERIAL AND DIMENSIONS

|            |                          |
|------------|--------------------------|
| Dimensions | <b>150 x 126 x 27 mm</b> |
| Net weight | <b>230 g</b>             |

#### POWER CONSUMPTION

|            |                 |
|------------|-----------------|
| Power mode | <b>DC</b>       |
| Voltage    | <b>9V ~ 16V</b> |
| Amperage   | <b>1500mA</b>   |

#### CERTIFICATION

|                     |                |
|---------------------|----------------|
| Grade               | <b>3</b>       |
| Normative           | <b>EN50131</b> |
| Environmental class | <b>II</b>      |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-10 °C ~ 55 °C</b> |
| Maximum humidity      | <b>93%</b>            |

