# technical datasheet



# XVIV

# Wireless panel HUB2PLUS-B

# ADDITIONAL FEATURES

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Automatic change from 2G to 3G	Sí
Change between SIM cards	Sí
Maximum number of connected IP cameras	100
Mobile devices	iOS 9.1 o posterior / Android 4.4 o posterior

#### POWER CONSUMPTION

Voltage	110V ~ 240V
Consumption (w)	10W
Built in battery	Yes
Battery life	± 15 horas
Battery support	Li-ion 3 A/h

## MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	350 g
Color	Black
ZONES	

# ZONES

Maximum number of rooms	50
Maximum number of devices	200

#### **PROCCESSOR**

Processor	ARM
Operating system	OS Malevich

# PARTITIONS AND MEMORIES

Maximum users 2	200
-----------------	-----

## COMMUNICATION

IP	Sí
GSM	Sí
3G	Sí
Wi-Fi	Sí
Communication with CRA	Yes, through contactID and SIA

#### VIA RADIO

Frequency	868.0 MHz ~ 868.6 MHz
Transmission	Up to 2000 m (without
distance	obstacles)
Maximum power RF	Potencia maxima RF

#### **AMBIENT**

Operating temperature	-10 °C ~ 40 °C
Use	Indoor

#### CERTIFICATION

0.446	_
Normative	EN50131

### SPECS AND FEATURES

Type of Central	Wireless
Type of certifial	VVIICICS

# SABOTAGE

Wall tamper Sí

