



P ▲ R ▲ D O X

Hybrid panel

MG5075

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
3G	Si
Mobile Network	GPRS / GSM (with PCS module)

POWER CONSUMPTION

Power mode	DC
Voltage	100V ~ 240V
Amperage	1500mA
Battery support	Optional
Battery model	12V DC 4 ~ 7 ~ 24 Ah

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

ZONES

Maximum number of zones	32
Wired on-board zones	5

VIA RADIO

Frequency	433MHz / 868MHz
-----------	-----------------

ADDITIONAL FEATURES

Mobile app	INSITE GOLD
------------	-------------

MATERIAL AND DIMENSIONS

Dimensions	185 x 90 x 30 mm
Net weight	1250 g
Weight with packaging	1440 g

PARTITIONS AND MEMORIES

Partitions	2
User codes	32
Registration events	512

AMBIENT

Operating temperature	0 °C ~ 50 °C
Use	Indoor

SPECS AND FEATURES

Type of Central	Hybrid
-----------------	--------

PROGRAMMABLE OUTPUTS

Maximum of PGMs	16
-----------------	----

