



## P ▲ R ▲ D O X

Módulo expensor de 8 salidas programables

PGM82

### POWER CONSUMPTION

|                       |           |
|-----------------------|-----------|
| Power mode            | DC        |
| Voltage               | 11V ~ 16V |
| Amperage              | 315mA     |
| Relay voltage output  | 24V       |
| Relay Amperage output | 4000mA    |

### MATERIAL AND DIMENSIONS

|                       |                   |
|-----------------------|-------------------|
| Dimensions            | 165 x 102 x 25 mm |
| Net weight            | 215 g             |
| Weight with packaging | 250 g             |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -20 °C ~ 50 °C |
| Maximum humidity      | 95%            |

### ADDITIONAL FEATURES

|            |             |
|------------|-------------|
| Mobile app | INSITE GOLD |
|------------|-------------|

### SPECS AND FEATURES

|               |                                           |
|---------------|-------------------------------------------|
| Type          | Módulo expensor de 8 salidas programables |
| Compatibility | Spectra / Magellan / EVO                  |

### PROGRAMMABLE OUTPUTS

|       |   |
|-------|---|
| Board | 8 |
|-------|---|

### CERTIFICATION

|           |           |
|-----------|-----------|
| Normative | EN50130-4 |
|-----------|-----------|

### TECHNICAL CHARACTERISTICS

|               |    |
|---------------|----|
| LED indicator | Sí |
|---------------|----|

