



## AJAX

### Wireless panel

### HUB2-DC6V-W

#### ADDITIONAL FEATURES

Mobile app	<b>Ajax Security System</b>
SMS notification	<b>Si</b>
Call notification	<b>Si</b>
Notificación Push	<b>Si</b>
Maximum number of connected IP cameras	<b>25</b>
Mobile devices	<b>iOS 9.1 or later / Android 4.1 or later</b>
SIM card number	<b>2</b>
LED indicators	<b>Yes</b>

#### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>4.2V ~ 16V</b>
Built in battery	<b>Not</b>
Battery life	<b>± 16 hours</b>
Battery model	<b>6V DC</b>
Input current	<b>2200mA @4.2V DC / 500mA @16V DC</b>
Output current	<b>1500mA</b>

#### VIA RADIO

Frequency	<b>868mHz</b>
Transmission distance	<b>Up to 2000 m (without obstacles)</b>
Maximum power RF	<b>Class 4 (2W) / 850/900Mhz , Class 2 (1W) / 1800/1900MHz</b>

#### ZONES

Maximum number of rooms	<b>50</b>
Maximum number of devices	<b>100</b>

#### SPECS AND FEATURES

Type of Central	<b>Wireless</b>
-----------------	-----------------

#### SABOTAGE

Box tamper	<b>Si</b>
------------	-----------

#### MATERIAL AND DIMENSIONS

Dimensions	<b>163 x 163 x 36 mm</b>
Material	<b>ABS plastic</b>
Net weight	<b>360 g</b>
Color	<b>White</b>

#### COMMUNICATION

IP	<b>Si</b>
GPRS	<b>Si</b>
Communication with CRA	<b>Yes, through contactID and SIA</b>
Protocolo	<b>Jeweller</b>

#### AMBIENT

Operating temperature	<b>5 °C ~ 40 °C</b>
Use	<b>Indoor</b>

#### CERTIFICATION

Grade	<b>2</b>
Normative	<b>EN50131</b>

#### PARTITIONS AND MEMORIES

Maximum users	<b>50</b>
---------------	-----------

#### PROCESSOR

Operating system	<b>OS Malevich</b>
------------------	--------------------

