Alhua



Ip recorder of 4 channel and 12 mpx resolution

VIDEO

NVR2104HS-I2

RECORDING

RECORDING	
Maximum	
recording	12 Mpx
resolution	
Input bandwidth	80Mbps
Video compression	H.265 / H.264
Recording mode	Manual / Programmed / Motion Detection / Alarm
Audio compression	G.711A / G.711U / G.726 / PCM
Resolutions	12Mpx / 4K / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / D1
Output bandwidth	60Mbps
NETWORK FEATUR	ES
Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
	b Browser (ActiveX) / Smartphone
vision	App / Smart PSS Software
Software	SmartPSS
Арр	iDMSS / gDMSS
	-
INTELLIGENT VIDEO) SYSTEM
Line crossing	Yes
Intrusion	Yes
Privacy Mask	Yes
Face detection	Yes
SMD PLUS	Yes, 4 channels (human / vehicle classification)
Motion detection	Yes
AMBIENT	
Operating temperat	ture -10 °C ~ 55 °C
Use	Indoor
Maximum humidity	93%

STORAGE

Number of supported hard drives	1

MATERIAL AND DIMENSIONS

MATERIAL AND DIMI	
Installation	Desktop
Dimensions	260 x 232.7 x 47.6 mm
Material	Metal
Net weight	810 g
Weight with packagi	ng 1380 g
Chassis	Compact 1U
POWER CONSUMPT	ON
Power mode	DC
Voltage	12V
Consumption (w)	10W
Amperage	1500mA
VIDEO OUTPUT	
HDMI Output Numbe	er 1
Number of VGA outp	uts 1
Resolution HDMI	4K
Similar video signals	HDMI and VGA
REPRODUCTION ANI	D COPY OF SECURITY
Simultaneous	
cameras in reproduction	1/4
Playback bac	Pause / Stop / Fast forward / Fast kward / Rewind / Play by frame / reen / Backup (cut/file) / Partially enlarge / Audio on/off
Backup mode	USB
SYSTEM (RECORDER	S)
Processor	Industrial grade integrated processor
Operating system	Embedded LINUX
Smart fan	Yes
SPECS AND FEATUR	ES
Technology	IP
Serie	Serie 2

technical datasheet

2

Maximum haro	d disk size (Unit) 10 TB
Type HDD	3,5 SATA"
FACE RECOGN	IITION
Number of faces	4 faces processed per second
Number of channels with facial recognition	1 channel video face recognition
Database managment	Up to 10 databases with 5,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image.
AUDIO	
Audio Inputs	1
Audio Outputs	

INPUTS/OUTPUTS

USB 2.0

IP Channels

PERIMETER PROTECTION

Channels number with analytics

1 channel

4

