



5 in 1 (hd-cvi, hd-tvi, ahd, analog and ip) recorder of 4 channel and 2 mpx maximum resolution

XVR5104HE-I3

RECORDING

Maximum recording resolution	2 Mpx
Video compression	H.265+ / H.265 / H.264+ / H.264
Resolution HDCVI recording	2 Megapixel (1080p)
Resolution HDTVI recording	2 Megapixel (1080p)
Resolution recording AHD	2 Megapixel (1080p)
Images per second Main stream	5Mpx-N (1 ~ 10fps) / 4Mpx-N / 1080P (1 ~ 15fps) / 1080N / 720P / 960H / D1 / CIF (1 ~ 25fps)
Images per second Extra stream	D1 / CIF (1 ~ 15fps)
Video bit rate	32Kbps ~ 6144Kbps per channel
Audio compression	G.711A / G.711U / PCM
Frecuencia muestreo audio	8KHz / 16KHz
Speed audio bits	64Kbps per channel

VIDEO

BNC channels	4
IP Channels	6, replacing the BNC channels
Accepted IP cameras	4 BNC cameras + 2 IP cameras
Video formats	HDCVI / TVI / AHD / CVBS / IP
Admitted resolutions HDCVI	5Mpx / 4Mpx / 2Mpx / 1Mpx
Admitted resolutions HDTVI	5Mpx / 4Mpx / 2Mpx / 1Mpx
Admitted resolutions AHD	5Mpx / 4Mpx / 2Mpx / 1Mpx
Cameras CVBS	Yes
Resolution IP cameras	6 Megapíxeles

INTELLIGENT VIDEO SYSTEM

IoT	Yes
-----	------------

NETWORK FEATURES

Number of ports RJ45	1
Velocità RJ45	10 / 100 Mbps
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser (ActiveX) / Smartphone App / Smart PSS Software
Software	SmartPSS
App	iDMSS / gDMSS

MATERIAL AND DIMENSIONS

Installation	Desk / Rack
Dimensions	325 x 257 x 55 mm
Material	Metal
Net weight	1100 g
Weight with packaging	1800 g
Chassis	Mini 1U

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	4W
Amperage	1500mA

INPUTS/OUTPUTS

Alarm input	8
USB 2.0	2
RS485	1
Alarm output	3

AUDIO

Audio Inputs	4
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

STORAGE

Number of supported hard drives	1
Maximum hard disk size (Unit)	16 TB

technical datasheet

POS	Yes
Face detection	Yes

SMD PLUS	Yes, 4 channels (human / vehicle classification) (analog cameras only)
----------	---

Motion detection	Yes
------------------	------------

Video Tamper	Yes
--------------	------------

VIDEO OUTPUT

HDMI Output Number	1
--------------------	----------

Number of VGA outputs	1
-----------------------	----------

Resolution HDMI	1080P
-----------------	--------------

Resolución VGA	1080P
----------------	--------------

AMBIENT

Operating temperature	-10 °C ~ 55 °C
-----------------------	-----------------------

Use	Indoor
-----	---------------

Maximum humidity	90%
------------------	------------

REPRODUCTION AND COPY OF SECURITY

Backup mode	USB / Network device
-------------	-----------------------------

Nº canales simultáneos con cámaras IP	1 / 4 / 6
---------------------------------------	------------------

Nº canales simultáneos sin cámaras IP	1 / 4
---------------------------------------	--------------

SPECS AND FEATURES

Technology	5 IN 1 (HD-CVI, HD-TVI, AHD, analog and IP)
------------	--

Serie	Serie 5
-------	----------------

FACE RECOGNITION

Number of channels with facial recognition	1 channel video face recognition (only analog cameras)
--	---

Database managment	Up to 10 databases with 10,000 faces in total / Allows designating name / gender / birth date / nationality / address / Identification information can be added to each face image.
--------------------	--

Type HDD	3,5 SATA"
----------	------------------

SYSTEM (RECORDERS)

Processor	Industrial grade integrated processor
-----------	--

Operating system	Embedded LINUX
------------------	-----------------------

PERIMETER PROTECTION

Channels number with analytics	2 channels / 10 IVS rules for each channel (analog cameras only)
--------------------------------	---

