technical datasheet





Ip recorder of 16 channel and 12 mpx resolution with 16 PoE ports

NVR2216-16P-I

NETWORK FEAT	URES	FACE RECOC	GNITION		
PoE ports	16	Number of	8 faces processed per second		
Number of	1	faces Number of			
ports RJ45	<u>'</u>	channels			
Speed RJ45	10 / 100 / 1000 Mbps	with facial	1 channel video face recognition		
Mobile	Android / IOS (Apple)	recognition			
devices	, шалела , тее (търге)	Strange mode	Notice of faces not registered in the database		
ONVIF	Yes	Search Al	database		
Remote vision	Web Browser (ActiveX) / Smartphone App / Smart PSS Software	(artificial intelligence)	Up to 8 simultaneous faces		
Type PoE	802.3af	<u>g, </u>	Up to 10 databases with 5,000 faces in		
PoE	25.5W per port / 130W in total	Database	total / Allows designating name / gender / birth date / nationality / address / Identification information can		
consumption	25.5vv per port / 150vv III total	managment			
Арр	iDMSS / gDMSS		be added to each face image.		
RECORDING		Database application	Each database can be applied to video channels independently.		
Maximum		Actions	<u> </u>		
recording	12 Mpx	available	Buzzer / voice prompts / email / snapshot / recording / alarm output /		
resolution		after	PTZ activation		
Input bandwidth	200Mbps	detection			
Video compressi		POWER CON	POWER CONSUMPTION		
Recording mode	Manual / Programmed / Motion Detection / Alarm	Power mode	AC		
Audio compressi	G.711A / G.711U / G.726 / AAC /	Voltage	100V ~ 240V		
	РСМ	Consumption	(w) 10W		
Resolutions 12Mpx / 4K / 5Mpx / 4Mpx / 3Mpx / 1080P / 720P / D1		Amperage	age 3500mA		
Output bandwid	th 100Mbps	REPRODUCT	TON AND COPY OF SECURITY		
MATERIAL AND	DIMENSIONS	Simultaneou	Simultaneous		
Installation	Desk / Rack	cameras in	1/4/8/9/16		
		reproduction	Play / Pause / Stop / Fast forward / Fast		
Dimensions Material	375 x 329.3 x 53 mm	Playback	backward / Rewind / Play by frame / Full screen / Backup (cut/file) / Partially enlarge / Audio on/off		
	Metal	functions			
Net weight	2650 g	Backup	USB		
Weight with pac	kaging 3910 g	mode			
Chassis	10	Synchronized playback	16		
AMBIENT		p.a., 2001			
Operating tempe	erature -10 °C ~ 55 °C	INPUTS/OUT	PUTS		
Use	Indoor	Alarm input	4		
Maximum humidity 9		USB 2.0	USB 2.0 2		
VIDEO OUTPUT		Alarm outpu	t 2		

technical datasheet

HDMI Output Nu	umber 1	Number of supported hard drives			
Number of VGA outputs 1		Number of supported hard drives		2	
Resolution HDMI 4K		Maximum hard disk size (Unit)		8 TB	
Resolution ADM	46	Type HDD		3,5 SATA"	
PERIMETER PRO	TECTION				
Channels		GENERAL INFOR	RMATION		
number with	2 channels	Serie		Wiz Sense	
analytics		Technology		IP	
Type of	Human secondary recognition /	recritiology		IP	
identification	vehicle for line crossing and intrusion	AUDIO			
Smart search	Search by classification (Human /	Audio Inputs		1	
Siliait sealeil	Vehicle)	Audio Outputs		1	
VIDEO					
ID Champala		INTELLIGENT VIDEO SYSTEM			
IP Channels	16	Face		Yes	
Resolution IP cameras 12 Megapíxeles		detection		165	
SYSTEM (RECOR	DERS)	SMD PLUS	Yes, 4 channels (h	numan / vehicle classification)	
Processor	Industrial grade integrated processor				
Operating system	Embedded LINUX				

