

**AJAX**Wired volumetric and glass
break detector**COMBIPROTECT-FIBRA-B****DETECTION**

Detector type	Wired
Detection distance	12 m
Angle detection	88.5° Horizontal / 80° Vertical
Installation height	2.4 m
Detection speed	0,3 m/s ~ 2 m/s
Pets immunity	Up to 20 kg and 50 cm
Sensitive element	Electret microphone
Glass break detection	Sí, hasta 9 metros
Microphone	180° coverage
Detection technology	Volumetric and glass break

ESPECIFICACIONES TÉCNICAS

Compatibility	Ajax Fibra panels
LED indicators	Sí
Tamper	Sí
Connection type	BUS
Protection against false alarms	Yes, algorithmic analysis
Transmission distance	Up to 2000 m

POWER CONSUMPTION

Power mode	DC (via Hub Hybrid BUS)
Voltage	24V

SENSOR

Type of sensor	PIR and microphone
PIR sensitivity	Selectable LO / MID / HI

MATERIAL AND DIMENSIONS

Dimensions	110 x 103 x 81 mm
Material	Plastic
Net weight	80 g
Weight with packaging	120 g
Color	White

AMBIENT

Operating temperature	-10 °C ~ 40 °C
Degree of protection	IP50
Use	Indoor
Maximum humidity	75%

CERTIFICATION

Grade	2
Normative	EN50131

