



HIKVISION
accessories

Control de acceso y videoportero indoor-outdoor with qr-code / card mifare 13.56mhz

DS-K1T500S

FEATURES

Communication	1 RS-485/1 RS-232
Integrated controller	Si
Sound warning	Si
Camera	2 Mpx
Face detection	Yes
Screenshot	Yes
Integrated microphone	Yes, sensitivity -25 ± 3db
Integrated speaker	Yes

INPUTS/OUTPUTS

Alarm input	2
Door sensor	1
Botón de salida	1
Blocking output	1
Alarm output	1
Bell	1

AMBIENT

Operating temperature	-40 °C ~ 70 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	90%

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	32 bits
Software	iVMS-4200
SD card	Up to 128G
Storage System	NVR / Micro SD

SPECS AND FEATURES

Serie	Hika-P
Control type	Control de acceso y videoportero

IDENTIFICATION

Mode	QR-Code / Card
Type of card	MIFARE 13.56MHZ
Maximum reading distance	≥ 2 cm
Number of cards	50000
NUmber of register	200000
Identificación remota	Si

MATERIAL AND DIMENSIONS

Installation	Wall
Dimensions	218 x 78 x 41 mm
Material	Metal
Net weight	500 g

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Amperage	1000mA

FUNCTIONS

Duress alarm	Si
Antipassback	Si
Tamper	Yes

COMMUNICATION

Communication mode to the reader	Wiegand 26 / 34 / RS485
Mode	TCP / IP / RS485

