



HIKVISION®

Minidome 4 in 1 (cvi, tvi, ahd and analog) camera of 5 megapixels and fix lens

DS-2CE76H0T-ITMF

VIDEO (CAMERAS)

| | |
|-------------------|--|
| Video Resolution | 5 Megapixels |
| BLC | Yes |
| HLC | Yes |
| 2D-NR | Yes |
| AGC | Yes |
| AWB | Yes |
| WDR | DWDR |
| Images per second | 20fps |
| Video output | 1 x BNC switchable HD-CVI / HD-TVI / AHD / CVBS |
| Day / night mode | Colour |
| Mirror | On / Off |

POWER CONSUMPTION

| | |
|-----------------|--------------|
| Power mode | DC |
| Voltage | 12V |
| Consumption (w) | 4.3W |
| Amperage | 360mA |

NIGHT VISION

| | |
|-----------------------|-------------|
| Night vision distance | 30 m |
| Type of night vision | IR |
| Smart IR | Yes |
| EXIR | Yes |

DISTANCE DORI

| | |
|-----------|-------------|
| Detect | 69 m |
| Observe | 27 m |
| Recognize | 14 m |
| Identify | 7 m |

LENS

| | |
|----------------|---------------|
| Lens Type | Fix |
| Focal distance | 2.8 mm |
| Angle of View | 85° |

IMAGE

| | |
|--------------------------|--------------------------|
| Sensor | CMOS® |
| Sensor resolution | 2560 x 1944 |
| Electronic shutter speed | 1/25s ~ 1/50,000s |
| Minimum lighting | 0.01Lux |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -40 °C ~ 60 °C |
| Degree of protection | IP67 |
| Use | Indoor-outdoor |
| Maximum humidity | 90% |

MATERIAL AND DIMENSIONS

| | |
|-----------------------|----------------------------|
| Dimensions | 82.6 x 90 x 79.4 mm |
| Material | Metal |
| Net weight | 290 g |
| Weight with packaging | 350 g |

GENERAL INFORMATION

| | |
|----------------|--|
| Serie | PRO |
| Technology | 4 IN 1 (CVI, TVI, AHD and analog) |
| Type of camera | Minidome |

AXES

| | |
|--------|---------------|
| Motion | 3-Axis |
|--------|---------------|

