

P ▲ R ▲ D O X



wired panel with 8 on-board zones

SP6000+

COMMUNICATION

External voice module	Yes, with VDMP3 module
IP	Yes, with IP150 module
GPRS	Yes, with PCS module
GSM	Yes, with PCS module
Programming	Installer, teacher and maintenance
Expansion bus	Yes, 4 wires

POWER CONSUMPTION

Power mode	AC
Voltage	16.5V
Amperage	2000mA
Battery support	Sí, 12V 4 ~ 7 Ah
Standby consumption	55mA

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	II

PARTITIONS AND MEMORIES

Partitions	2
User codes	32

SPECS AND FEATURES

Type of Central	Wired
-----------------	-------

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

ZONES

Maximum number of zones	32
Wired on-board zones	8
ATZ (Double zones)	Sí, hasta 16 zonas

ADDITIONAL FEATURES

Calendar	Sí
Software Update	Sí
Mobile app	INSITE GOLD

PROGRAMMABLE OUTPUTS

Board	2
Maximum of PGMs	16

MATERIAL AND DIMENSIONS

Dimensions	190 x 90 mm
------------	-------------

