technical datasheet



P A R A D O X

Wireless curtain volumetric detector

NV37MR

Interruptores DIP

DETECTION	
Detector type	Wireless
Detection distance	10 m
Angle detection	5.7°
Installation height	2 m
Coverage	Pets immunity mode: 7.5 x 2 m / Sharp Mode: 10 x 2 m
Pets immunity	Up to 50 cm
Antimasking	Detection up to 7.5 cm
PIR detection advance at ground level (PIR Creep)	Sí
Detection technology	Curtain volumetric
MATERIAL AND DIMENSI	ONS
Dimensions	123 x 61 x 43 mm
Net weight	150 g
Weight with packaging	100
	170 g
ESPECIFICACIONES TÉCN	, and the second
ESPECIFICACIONES TÉCN LED indicators	, and the second
	IICAS
LED indicators	IICAS Sí
LED indicators LED colors	NICAS Sí Verde / Rojo

Sensitivity adjustment

AMBIENT

Operating temperature	-40 °C ~ 70 °C
Degree of protection	IP54
Use	Indoor-outdoor
Maximum humidity	95%

CERTIFICATION

Grade	2
Normative	EN50131
Environmental class	IV

POWER CONSUMPTION

Battery model	2 x AA
Battery duration	Up to 3 años

VIA RADIO

Frequency 868mHz

