



HIKVISION
HiWatch Series

Minidome ip camera of 2 megapixels and fix lens

HWI-D120HA

VIDEO (CAMERAS)

Resolución vídeo	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	1080P / 720P (1 ~ 25fps)
Sub stream	640 × 480 / 640 × 360 (1 ~ 25fps)
Watermark	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Resolución sensor	1920 x 1080
Sensor Size	1/2.9"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.01Lux
Ratio S / N	Más de 52dB

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	104°
Filtro IR	Sí

NIGHT VISION

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.5W
Amperage	400mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK10
Use	Indoor-outdoor
Maximum humidity	95%

DISTANCE DORI

Detect	42 m
Observe	16 m
Recognize	8 m
Identify	4 m

VIDEO ANALYSIS

Tipo de deteccion	Detección avanzada (clasificación persona/vehículo)
Video Tamper	Sí
Classification	Sí
Human / vehicle	

technical datasheet

Night vision distance	30 m
Tipo de visión nocturna	IR
EXIR	Yes
Wavelength	850 nm

MATERIAL AND DIMENSIONS

Dimensions	84.7 x 110.8 (Ø) mm
Material	Metal and plastic
Net weight	360 g
Weight with packaging	520 g

SPECS AND FEATURES

Technology	IP
Type of camera	Minidome
Serie	HiWatch

Motion detection 2.0	Yes (human and vehicle)
-------------------------	--------------------------------

AXES

Motion	2-Axis
--------	---------------

STORAGE

Storage Systems	FTP
-----------------	------------

