



Video analytics gateway with 4  
channels

66000004

# technical datasheet

## VIDEO

|                          |                                                                                                  |
|--------------------------|--------------------------------------------------------------------------------------------------|
| IP Channels              | 4                                                                                                |
| Resolution<br>IP cameras | 2 Megapíxeles                                                                                    |
| Maximum<br>resolution    | 1080P, 25fps (con analítica de vídeo desactivada) / 4CIF, 5fps (con analítica de vídeo activada) |
| ONVIF                    | Yes, S and T type                                                                                |
| Bandwidth                | 2Mbps (with video analytics disabled) / 1Mbps (with video analytics enabled)                     |
| Video<br>compression     | H.264 / H.265                                                                                    |

## NETWORK FEATURES

|                      |                             |
|----------------------|-----------------------------|
| Number of ports RJ45 | 1                           |
| Velocità RJ45        | 10 / 100 Mbps               |
| Mobile devices       | Android / IOS (Apple)       |
| P2P                  | Si                          |
| Software             | ADPRO VideoCentral Platinum |
| App                  | iTrace                      |

## INTELLIGENT VIDEO SYSTEM

|                  |     |
|------------------|-----|
| Motion detection | Yes |
| Video Tamper     | Yes |
| IntrusionTrace™  | Yes |
| LoiterTrace™     | Yes |

## AUDIO

|                                   |                                  |
|-----------------------------------|----------------------------------|
| Audio Inputs                      | Through compatible cameras       |
| Audio Outputs                     | 1 and through compatible cameras |
| Audio bidirectional (Full-duplex) | Yes                              |

## GENERAL INFORMATION

|            |                         |
|------------|-------------------------|
| Technology | IP                      |
| Type       | Video analytics gateway |

## STORAGE

|           |                         |
|-----------|-------------------------|
| SD card   | Yes, from 32Gb to 256Gb |
| Recording | Analytical events       |

## SYSTEM (RECORDERS)

|                  |                     |
|------------------|---------------------|
| Operating system | ADPRO® XO™ Security |
|------------------|---------------------|

## POWER CONSUMPTION

|                       |        |
|-----------------------|--------|
| Power mode            | DC     |
| Voltage               | 5V     |
| Amperage              | 2000mA |
| Power supply included | Yes    |

## AMBIENT

|                       |              |
|-----------------------|--------------|
| Operating temperature | 0 °C ~ 70 °C |
| Use                   | Indoor       |
| Maximum humidity      | 90%          |

## MATERIAL AND DIMENSIONS

|                       |                         |
|-----------------------|-------------------------|
| Dimensions            | 101.6 x 101.6 x 23.6 mm |
| Net weight            | 160 g                   |
| Weight with packaging | 510 g                   |

## INPUTS/OUTPUTS

|              |                      |
|--------------|----------------------|
| Alarm input  | With external module |
| USB 2.0      | 2                    |
| Alarm output | With external module |

## WI-FI

|                 |                      |
|-----------------|----------------------|
| Wi-Fi standard  | IEEE802.11 b / g / n |
| Frequency range | 2.4 GHz              |

## VIDEO OUTPUT

|                    |   |
|--------------------|---|
| HDMI Output Number | 1 |
|--------------------|---|

