



10 ports switch with 8 PoE ports

VK-SWITCH-1008POE-120-G

POWER CONSUMPTION

Power mode	AC
Voltage	100V ~ 240V
Amperage	2200mA
Standby consumption	6W
Consumption On	120W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	120W
Power supply included	Yes

ETHERNET PORTS

POE ports	8
Uplink ports	2
10 / 100 / 1000 Base-T	8
POE Ports Speed	10 / 100 / 1000
Uplink ports speed	10/100/1000
Number of Ethernet ports	10

MATERIAL AND DIMENSIONS

Installation	Desk / wall
Dimensions	195 x 130 x 40 mm
Material	Metal
Net weight	690 g
Weight with packaging	920 g

SYSTEM (SWITCH)

MAC address table	2K
-------------------	----

AMBIENT

Operating temperature	-20 °C ~ 55 °C
Degree of protection	IP30
Use	Indoor
Maximum humidity	90%
Lightning protection	4KV

CHARACTERISTICS (SWITCH)

Data rate supported	20 Gbps
Packet redirection speed	14.88 Mpps
Maximum transmission distance	100 m
Buffer Memory	2 Mb

NET STANDARD

IEEE802,3af	Yes
IEEE802,3at	Yes

