



HIKVISION
accessories

Ip video door station with camera

DS-KD8003-IME1

CAPACITY

Cards	10000
Register	2000
Linked gates	2
Linked phones	8
Extensiones interiores vinculadas	500
Número máximo de sub módulos	7

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	10W
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	98 x 99.8 x 43.9 mm
Net weight	290 g
Weight with packaging	500 g

INPUTS/OUTPUTS

Alarm input	4
Botón de salida	2
Conector de módulo adicional	1

SYSTEM (RECORDERS)

Processor	Embedded MCU Processor
Operating system	Embedded LINUX

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	TCP / IP / RSTP
IP connection	10 / 100Mbps autoadaptive

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	180°
Night vision	Sí
Day / Night	ICR
Video compression	H.264

AMBIENT

Operating temperature	-40 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Audio compression	G.711u

SPECS AND FEATURES

Technology	IP
Type	IP Video Door Station with camera

OPENING

Call elements	Simple button
Mode	Card / Application / Indoor Monitor

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Sí
--------	-----------