



HIKVISION
accessories

2-wire video intercom with camera

DS-KD8003Y-IME2

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	2
Botón de salida	2
Blocking output	2
Conector de módulo adicional	1

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Use	Indoor-outdoor
Maximum humidity	90%

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX
RAM	256 MB
ROM	32 MB

POWER CONSUMPTION

Power mode	Powered via DS-KAD704Y
Consumption (w)	4W
Power output	DC 12V

AUDIO (VIDEO INTERCOM)

Sound input	Multidirectional microphone
Sound output	Built-in speaker
Audio compression	G.711A / G.711U

OPENING

Call elements	Simple button
---------------	---------------

MATERIAL AND DIMENSIONS

Installation	Surface / embed
Dimensions	100 x 98 x 42 mm
Net weight	380 g
Weight with packaging	510 g

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	146°
Day / Night	ICR
Video compression	H.264

CAPACITY

Register	2000
Linked gates	500
Número máximo de sub módulos	16

GENERAL INFORMATION

Technology	2 Wire
Type	2-wire Video Intercom with camera

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Tamper	Si
--------	----

