



## AJAX

### Switchable switch panel

### SOLOBUTTON-1G2W-IVO

#### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 40 °C |
| Degree of protection  | IP20           |
| Use                   | Indoor         |
| Maximum humidity      | 75%            |

#### MATERIAL AND DIMENSIONS

|                       |                |
|-----------------------|----------------|
| Dimensions            | 81 x 81 x 8 mm |
| Net weight            | 45 g           |
| Weight with packaging | 60 g           |
| Color                 | Ivory          |

#### SPECS AND FEATURES

|               |                                                                              |
|---------------|------------------------------------------------------------------------------|
| Type          | Switchable switch panel                                                      |
| Compatibility | Hub Plus / Hub 2 (2G / 4G) / Hub 2 Plus / Hub Hybrid (2G / 4G) / ReX / Rex 2 |

#### POWER CONSUMPTION

|            |                               |
|------------|-------------------------------|
| Power mode | Powered via relay (LightCore) |
|------------|-------------------------------|

#### VIA RADIO

|                                                 |                        |
|-------------------------------------------------|------------------------|
| Frequency                                       | 868.0 MHz ~ 868.6 MHz  |
| Maximum power RF                                | Hasta 20 mW            |
| Maximum distance between the device and the hub | 1100 m (in open space) |

#### SPECIFICATIONS (LIGHT SWITCHES)

|                   |                  |
|-------------------|------------------|
| Contactless panel | Yes, up to 15 mm |
| Backlight         | Yes, optional    |

