



Minidome ip camera of 4 megapixels and optical zoom lens

IPC-HDW2441T-ZS

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	20fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	H.264: 32Kbps ~ 6144Kbps / H.265: 12Kbps ~ 6144Kbps
Compression	H.265 / H.264
Main stream	2688 × 1520 (1 fps-20 fps) / 2560 × 1440 (1 fps-25/30 fps)
Sub stream	704 × 576
Watermark	Yes
Mirror	On / Off

DISTANCE DORI

Detect (Open lens)	64 m
Detect (Closed Lens)	210 m
Observe (Open lens)	26 m
Observe (Closed lens)	84 m
Recognize (Open lens)	13 m
Recognize (Closed lens)	42 m
Identify (Open lens)	6 m
Identify (Closed lens)	21 m

IMAGE

Sensor	CMOS ®
Resolución sensor	2688 x 1520
Sensor Size	1/2.9"

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, S and T type
Maximum number of users	6 users
Web browser	Explorer / Chrome / Firefox
Management software	Smart PSS / DSS / DMSS
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes
Cybersecurity	Yes

VIDEO ANALYSIS

Tipo de deteccion	Analytical with human/vehicle classification in line/area crossing
Crossing line	Yes
Intrusion	Yes
Motion detection	Yes (4 areas)
Audio detection	Yes
Video Tamper	Sí
Classification Human / vehicle	Sí
SMD PLUS	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6.1W
Amperage	520mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Optical zoom
Focal distance	2.7 mm ~ 13.5 mm
Maximum diaphragm opening	F/1.5
Angle of View	104° ~ 29°
Minimum focus distance	800mm

technical datasheet

Electronic shutter speed	1/3 ~ 1/100000s
--------------------------	-----------------

Minimum lighting	Color: 0.008Lux / B/W: 0.0008Lux
------------------	----------------------------------

Ratio S / N	More than 56dB
-------------	----------------

NIGHT VISION

Night vision distance	40 m
-----------------------	------

Tipo de visión nocturna	IR
-------------------------	----

Number of LEDs	2
----------------	---

IR ON/Off	Automatic / Manual
-----------	--------------------

Starlight	Yes
-----------	-----

AMBIENT

Operating temperature	-30 °C ~ 60 °C
-----------------------	----------------

Degree of protection	IP67
----------------------	------

Use	Indoor-outdoor
-----	----------------

Maximum humidity	95%
------------------	-----

SPECS AND FEATURES

Technology	IP
------------	----

Type of camera	Minidome
----------------	----------

Serie	Serie 2X41
-------	------------

AUDIO(CAMERAS)

Built in microphone	Yes
---------------------	-----

Audio compression	G.711A / G.711U / G.726 / PCM
-------------------	-------------------------------

MATERIAL AND DIMENSIONS

Dimensions	108.3 x 122 (Ø) mm
------------	--------------------

Material	Metal
----------	-------

Net weight	690 g
------------	-------

Weight with packaging	860 g
-----------------------	-------

STORAGE

MicroSD-Card	Up to 256Gb
--------------	-------------

Storage Systems	FTP / SFTP / Micro SD
-----------------	-----------------------

Storage anomaly	Yes
-----------------	-----

SYSTEM (CAMERAS)

Ram memory	128 MB
------------	--------

ROM memory	128 MB
------------	--------

AXES

Motion	3-Axis
--------	--------

