



2 wires / ip 7" monitor VTH5422HW-W



POWER CONSUMPTION

Power mode	DC
Voltage	48V
Amperage	1250mA
Standby consumption	2W
Consumption On	6W
Power output	DC 12V

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	189 x 130 x 26.9 mm
Material	ABS plastic + Polycarbonate
Net weight	35 g
Weight with packaging	560 g
Color	White

INPUTS/OUTPUTS

Alarm input	6
RS485	1
Alarm output	1
Bell	1

AUDIO (VIDEO INTERCOM)

Sound input	1
Sound output	Built-in speaker
Bidirectional audio	Sí
Audio compression	G.711A/G.711U/PCM

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

Do not disturb mode	Yes
Message recording if no response	Yes (SD card required)

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Network protocol	RTSP / RTP / SIP / DNS / SSH
Memory slot	SD hasta 64Gb
Wi-Fi	Sí
Tipo de Wi-Fi	IEEE802.11 b / g / n
ONVIF	Yes

SCREEN

Type	TFT
Size	7"
Resolution	1024 x 600
Touch	Sí

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	95%

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX

GENERAL INFORMATION

Technology	2 Wires / IP
------------	--------------

