

HIKVISION®

Ip recorder of 4 channel and 12
mpx resolution with 4 PoE ports

DS-7604NXI-K1/4P

NETWORK FEATURES

PoE ports	4
Number of ports RJ45	1
Velocità RJ45	10 / 100 / 1000 Mbps
Maximum number of users	128
Mobile devices	Android / IOS (Apple)
ONVIF	Yes
Remote vision	Web Browser / Smartphone App and Hik-Connect Software.
Type PoE	802.3at / af
PoE consumption	50W
Software	IVMS
App	Hik-Connect

VIDEO OUTPUT

HDMI Output Number	1
Number of VGA outputs	1
Resolution HDMI	4K
Resolución VGA	1080P
Similar video signals	HDMI and VGA

MATERIAL AND DIMENSIONS

Dimensions	320 x 240 x 48 mm
Material	Metal
Net weight	1170 g
Weight with packaging	2070 g

AUDIO

Audio Inputs	1
Audio Outputs	1
Audio bidirectional (Full-duplex)	Yes

GENERAL INFORMATION

Serie	Acusense
Technology	IP

INTELLIGENT VIDEO SYSTEM

Classification Human / vehicle	Yes
--------------------------------	------------

RECORDING

Maximum recording resolution	12 Mpx
Input bandwidth	40Mbps
Video compression	H.265+ / H.265 / H.264+ / H.264
Audio compression	G.711A / G.711U / G.722 / G.726 / AAC
Resolutions	12Mpx / 4K / 6Mpx / 5Mpx / 4Mpx / 3Mpx / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Output bandwidth	80Mbps

POWER CONSUMPTION

Power mode	DC
Voltage	48V
Consumption (w)	10W
Amperage	1350mA

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

STORAGE

Number of supported hard drives	1
Maximum hard disk size (Unit)	10 TB
Type HDD	3,5 SATA"

REPRODUCTION AND COPY OF SECURITY

Búsqueda inteligente	Yes
Synchronized playback	4

FACE RECOGNITION

Number of channels with facial recognition	1 channel video face recognition / 2 channels facial photo recognition
Database managment	Up to 16 databases with 20,000 faces in total

INPUTS/OUTPUTS

USB 2.0	2
---------	----------

Motion detection

Yes, 2.0

VIDEO

IP Channels

4

PERIMETER PROTECTION

Channels number with analytics

1 channel

