



Bullet ip camera of 8 megapíxeles and fix lens

HWI-B480H

VIDEO (CAMERAS)

Resolución vídeo	8 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	12.5fps@4K
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 16Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4K (1 ~ 12.5fps) / 5Mpx (1 ~ 20fps) / 4Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Watermark	Yes
Anti flap	Yes
Mirror	On / Off

IMAGE

Sensor	CMOS ®
Resolución sensor	3840 x 2160
Sensor Size	1/2.8"
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	0.01Lux
Ratio S / N	Más de 52dB

NIGHT VISION

Night vision distance	50 m
Tipo de visión nocturna	IR
IR ON/Off	Automatic / Manual
EXIR	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6W
Amperage	500mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	4 mm
Maximum diaphragm opening	F/2.0
Angle of View	86°
Filtro IR	Sí

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

SPECS AND FEATURES

Technology	IP
Type of camera	Bullet
Serie	HiWatch

VIDEO ANALYSIS

technical datasheet

Wavelength	850 nm
------------	--------

DISTANCE DORI

Detect	107 m
Observe	42 m
Recognize	21 m
Identify	11 m

MATERIAL AND DIMENSIONS

Dimensions	206.6 x 83.7 x 80.7 mm
Material	Metal and plastic
Net weight	375 g
Weight with packaging	510 g

AXES

Motion	3-Axis
--------	--------

Tipo de deteccion	Detección de movimiento básica (diferencia de píxeles)
Motion detection	Yes
Video	
Tamper	Sí

