



Ptz ip camera of 2 megapixels and optical zoom lens

SD49225DB-HNY

VIDEO (CAMERAS)

Video Resolution	2 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Digital Zoom	16x
Privacy mask	Hasta 24 zonas / Hasta 8 en la misma vista
Anti fog system	Yes
Type of Codex	CBR / VBR
Bit rate	H.264: 1792Kbps ~ 8192Kbps / H.265: 512Kbps ~ 5632Kbps
Compression	H.265 / H.264
EIS	Yes
Main stream	1080P / 1.3Mpx / 720P (1 ~ 25fps)
Sub stream	D1 / VGA / CIF (1 ~ 25fps)
Sub stream 2	1080P / 1.3Mpx / 720P (1~ 25fps)

PTZ

Pan / Tilt Range	Horizontal 360° / Vertical -15 ~ 90° with autoflip
Manual speed control	Horizontal 0.1°/s ~ 80°/s / Vertical 0.1°/s ~ 80°/s
Speed between presets	Horizontal 80°/s / Vertical 80°/s
Memories	300
PTZ mode	8 Tour between established points, 5 rounds
Protocol	DH-SD, Pelco-P/D
Flip	180°
Position after power failure	Return to the position before the fault

VIDEO ANALYSIS

Detection type	Analytical with human/vehicle classification in line/area crossing
Funciones IA	Detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Motion detection	Yes
Abandoned object	Yes
Missing object	Yes
Audio detection	Yes
Video Tamper	Sí
Loitering detection	Sí
Classification Human / vehicle	Yes
Detección de parking	Yes
SMD 3.0	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S , G and T
Transmission method	Unicast / Multicast
Maximum number of users	20 users
Web browser	Explorer / Chrome / Firefox / Safari
Management software	Smart PSS / DSS / DMSS / IVSS / ConfigTool / NVR / Imou
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

LENS

Lens Type	Optical zoom
Optical zoom	25x
Focal distance	4.8 mm ~ 120 mm
Maximum diaphragm opening	F/1.6 ~ F/3.5

technical datasheet

Idle mode **Preset / Pattern Scan / Tour**

DISTANCE DORI

Detect (Open lens)	75
Detect (Closed Lens)	1572 m
Observe (Open lens)	30 m
Observe (Closed lens)	624 m
Recognize (Open lens)	15 m
Recognize (Closed lens)	314 m
Identify (Open lens)	8 m
Identify (Closed lens)	157 m

IMAGE

Sensor	Starvis Cmos ®
Sensor resolution	1920 x 1080
Sensor Size	1/2.8'
Electronic shutter speed	1/1s ~ 1/30,000s
Minimum lighting	Color: 0.005Lux / B/W: 0.0005Lux
Ratio S / N	More than 55dB

NIGHT VISION

Night vision distance	100 m
Type of night vision	IR
Number of LEDs	3
IR ON/Off	Automatic / Manual
Smart IR	Yes
Starlight	Yes

MATERIAL AND DIMENSIONS

Dimensions	270.4 x 160 (Ø) mm
Net weight	2400 g
Weight with packaging	3910 g
Support included	Yes

AUDIO(CAMERAS)

Audio input	1 Input
Audio compression	G.711A / G.711U / G.722.1 / G.726 / G.729 / MPEG2-Layer2
Audio output	1

SYSTEM (CAMERAS)

Ram memory	256 MB
ROM memory	128 MB

Angle of View **58.5° ~ 2.8°**

Minimum focus distance **100mm ~ 1500mm**

Autofocus **Yes**

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	20W
Amperage	3000mA
PoE power	Yes
Type PoE	PoE+ 802.3at

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP66
Use	Indoor-outdoor
Maximum humidity	95%
Lightning protection	6KV

GENERAL INFORMATION

Serie	Wiz Sense
Technology	IP
Type of camera	PTZ

STORAGE

MicroSD-Card	Hasta 512Gb
Storage Systems	NAS / FTP / Micro SD
Storage anomaly	Yes

AXES

Motion **3-Axis**

INPUTS/OUTPUTS (CAMERAS)

Alarm **2 Entradas / 1 Salida**

