



MOVOK

Minidome ip camera of 4 megapixels and fix lens

VK-IPC-T141-L-B

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	DWDR
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Privacy mask	Up to 4 zones
Type of Codex	CBR / VBR
Bit rate	H.264 / H.265: 1792Kbps ~ 4Mbps
Compression	H.265 / H.264
Main stream	4Mpx (1 ~ 25fps)
Sub stream	D1 (1 ~ 25fps)
Mirror	On / Off

NIGHT VISION

Night vision distance	30 m
Tipo de visión nocturna	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light distance	20 m
White light	Si
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

MATERIAL AND DIMENSIONS

Dimensions	97 x 110 (Ø) mm
Material	Carcasa: metal / Anillo: plástico
Net weight	350 g
Weight with packaging	470 g
Color	Black

AMBIENT

IMAGE

Sensor	CMOS ®
Resolución sensor	2560 x 1440
Sensor Size	1/2.8'
Electronic shutter speed	1/25s ~ 1/1000s
Minimum lighting	0.01Lux
Ratio S / N	More than 56dB

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	3W
Amperage	250mA
PoE power	Yes
Type PoE	PoE 802.3af

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/2.0
Angle of View	102°

DISTANCE DORI

Detect	58 m
Observe	23 m
Recognize	12 m
Identify	6 m

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Web browser	Explorer
Management software	Smart PSS / ConfigTool (ambos en red local)

VIDEO ANALYSIS

Tipo de detección	Advanced detection (human classification)
SMD	Yes

technical datasheet

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

SPECS AND FEATURES

Technology	IP
Type of camera	Minidome
Serie	Serie 1

AXES

Motion	3-Axis
--------	--------

