

43



## MOVOK

Bullet ip camera of 5 megapixels and fix lens

VK-IPC-B351-AS-TI-B

### VIDEO (CAMERAS)

Video Resolution	<b>5 Megapixels</b>
BLC	<b>Yes</b>
HLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>WDR (140 dB)</b>
Images per second	<b>25fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Colour</b>
Privacy mask	<b>Up to 4 zones</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>3Kbps ~ 20480Kbps</b>
Compression	<b>H.265 / H.264</b>
Main stream	<b>5Mpx (1 ~ 25fps)</b>
Sub stream	<b>D1 (1 ~ 25fps)</b>
Sub stream 2	<b>720P (1 ~ 25fps)</b>
Mirror	<b>On / Off</b>

### VIDEO ANALYSIS

Detection type	<b>Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing</b>
Funciones IA	<b>Conteo de personas, mapa de calor, detección facial</b>
Crossing line	<b>Yes</b>
Intrusion	<b>Yes</b>
Face detection	<b>Yes</b>
Classification Human / vehicle	<b>Yes</b>
SMD	<b>Yes</b>

### POWER CONSUMPTION

Power mode	<b>DC</b>
Voltage	<b>12V</b>
Consumption (w)	<b>5.5W</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, G type</b>
Maximum number of users	<b>20 users</b>
Web browser	<b>Explorer / Chrome / Firefox</b>
Management software	<b>MOVOK (CMS)</b>
Mobile devices	<b>Android / IOS (Apple)</b>
Network disconnection	<b>Yes</b>
Conflict of IP addresses	<b>Yes</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Sensor resolution	<b>2880 x 1620</b>
Sensor Size	<b>1/2.7'</b>
Electronic shutter speed	<b>1/3 ~ 1/100000s</b>
Minimum lighting	<b>0.001Lux</b>
Ratio S / N	<b>More than 56dB</b>

### NIGHT VISION

Night vision distance	<b>40 m</b>
Type of night vision	<b>Dual light (IR+Luz blanca)</b>
IR ON/Off	<b>Automatic / Manual</b>
Starlight	<b>Yes</b>
White light	<b>Sí</b>
White light distance	<b>40 m</b>

### AMBIENT

Operating temperature	<b>-30 °C ~ 60 °C</b>
Degree of protection	<b>IP67</b>
Use	<b>Indoor-outdoor</b>
Maximum humidity	<b>95%</b>

### LENS

Lens Type	<b>Fix</b>
Focal distance	<b>2.8 mm</b>
Maximum diaphragm opening	<b>F/1.0</b>

# technical datasheet

Amperage	<b>460mA</b>
PoE power	<b>Yes</b>
Type PoE	<b>PoE 802.3af</b>

## MATERIAL AND DIMENSIONS

Dimensions	<b>224 x 77 x 76 mm</b>
Material	<b>Metal</b>
Net weight	<b>720 g</b>
Weight with packaging	<b>880 g</b>
Color	<b>Black</b>

## DISTANCE DORI

Detect	<b>60</b>
Observe	<b>24 m</b>
Recognize	<b>12 m</b>
Identify	<b>6 m</b>

## AUDIO(CAMERAS)

Built in microphone	<b>Yes</b>
Built in speaker	<b>Yes</b>
Audio compression	<b>G.711A / G.711U / G.726 / G.726ASF</b>

## SYSTEM (CAMERAS)

Ram memory	<b>128 MB</b>
ROM memory	<b>256 MB</b>

## AXES

Motion	<b>3-Axis</b>
--------	---------------

Angle of View	<b>111°</b>
---------------	-------------

## GENERAL INFORMATION

Serie	<b>Serie 3</b>
Technology	<b>IP</b>
Type of camera	<b>Bullet</b>

## STORAGE

MicroSD-Card	<b>Up to 256Gb</b>
Storage Systems	<b>FTP / Micro SD</b>
Storage anomaly	<b>Yes</b>

## TIOC

Siren	<b>Yes</b>
Light	<b>White</b>

