



## ANVIZ

Time and attendance control  
indoor with fingerprint /  
keyboard / card rfid 125khz

### VF30-PRO

#### IDENTIFICATION

|                          |                                      |
|--------------------------|--------------------------------------|
| Mode                     | <b>Fingerprint / Keyboard / Card</b> |
| Number of fingerprints   | <b>3000</b>                          |
| Type of card             | <b>RFID 125KHz</b>                   |
| Maximum reading distance | <b>5 cm</b>                          |
| Card reading time        | <b>less than 0.5 Sec</b>             |
| Number of cards          | <b>3000</b>                          |
| Scanning area            | <b>22 x 18 mm</b>                    |
| NUmber of register       | <b>100000</b>                        |

#### INPUTS/OUTPUTS

|             |          |
|-------------|----------|
| RS485       | <b>1</b> |
| Door sensor | <b>1</b> |
| Exit button | <b>1</b> |
| Relay NO/NC | <b>1</b> |
| Bell        | <b>1</b> |

#### FEATURES

|                       |                 |
|-----------------------|-----------------|
| Integrated controller | <b>Sí</b>       |
| LED indicator         | <b>Yes</b>      |
| Voice message         | <b>Sí</b>       |
| LCD screen            | <b>Sí, 2.4'</b> |

#### MATERIAL AND DIMENSIONS

|                       |                         |
|-----------------------|-------------------------|
| Dimensions            | <b>180 x 40 x 80 mm</b> |
| Net weight            | <b>250 g</b>            |
| Weight with packaging | <b>450 g</b>            |

#### COMMUNICATION

|        |            |
|--------|------------|
| TCP/IP | <b>Sí</b>  |
| Wi-Fi  | <b>Yes</b> |

#### POWER CONSUMPTION

|            |                    |
|------------|--------------------|
| Power mode | <b>DC</b>          |
| Voltage    | <b>12V</b>         |
| Amperage   | <b>1000mA</b>      |
| Type PoE   | <b>PoE 802.3af</b> |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-30 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP55</b>           |
| Use                   | <b>Indoor</b>         |
| Maximum humidity      | <b>90%</b>            |

#### FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

|                |                          |
|----------------|--------------------------|
| Main processor | <b>Linux</b>             |
| Software       | <b>Anviz CrossChex</b>   |
| Web server     | <b>Sí</b>                |
| CPU            | <b>1.0GHz High Speed</b> |

#### GENERAL INFORMATION

|                       |                                    |
|-----------------------|------------------------------------|
| Control type          | <b>Time and attendance control</b> |
| Compatible con A-TIME | <b>Yes</b>                         |

#### FUNCTIONS

|                 |           |
|-----------------|-----------|
| Schedule groups | <b>16</b> |
| Antipassback    | <b>Sí</b> |

