



5 ports cloud switch with 4 PoE ports

DS-3E1505P-EI

GESTIÓN REMOTA

P2P	Yes
Software	Hik Pro Connect / IVSM4200
Reiniciar switch	Yes
Reinicio de puerto PoE	Yes
Activación de modo extendido	Sí, de forma independiente por puerto
Modificación de la velocidad del puerto	Yes
Consumo de potencia real	Sí, total y por puerto
Histórico de pico máximo de consumo	Yes (up to 7 days)
Información de tráfico a tiempo real	Sí, por puerto
Información del dispositivo conectado	Sí para equipos Hikvision (IP, modelo y SN)
Diagrama de topología automático	Sí, para dispositivos Hikvision conectados

CHARACTERISTICS (SWITCH)

Data rate supported	10 Gbps
Packet redirection speed	7.44 Mpps
VLAN	Yes (max 32 VLAN)
DHCP	Sí
Maximum transmission distance	300 m
Buffer Memory	1 Mb
Mirror port	Sí
PoE Watchdog	Yes

ETHERNET PORTS

POE ports	4
Puertos Uplink	1
POE Ports Speed	10 / 100 / 1000
Uplink ports speed	10/100/1000
Number of Ethernet ports	5

NET STANDARD

IEEE802.3af	Sí
IEEE802.3at	Sí

POWER CONSUMPTION

Power mode	DC
Voltage	54V
Consumption (w)	65W
Amperage	1200mA
Standby consumption	≤ 0.9W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	60W

MATERIAL AND DIMENSIONS

Installation	Desk / wall
Dimensions	121.1 x 83.1 x 27.6 mm
Material	Metal
Net weight	220 g
Weight with packaging	750 g

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	2K
-------------------	-----------

