



HIKVISION
accessories

Indoor facial recognition terminal with keyboard and card

DS-K1T320MX

IDENTIFICATION

Mode	Facial / Keyboard / Card
Keyboard	Sí
Type of card	MIFARE 13.56MHz
Maximum reading distance	0 ~ 5 cm
Number of cards	1000
NUmber of register	100000
Number of faces	500
Face recognition distance	0.3 ~ 1.5 m
Face recognition speed	< 0.2 s
Autenticación múltiple	Sí
Anti-counterfeiting	Yes

FEATURES

Integrated controller	Sí
Tamper	Sí
LCD screen	Sí, 2.4"
Resolution LCD screen	320 x 240
Integrated speaker	Yes

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

CAMERA

Resolution	2 Mpx
Horizontal viewing angle	43°
Night vision	Yes, white light

INPUTS/OUTPUTS

USB 2.0	1
Door sensor	1
Botón de salida	1
Blocking entry	1
RJ45	1 x 10 / 100

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6W

MATERIAL AND DIMENSIONS

Dimensions	150 x 130 x 24.7 mm
Net weight	190 g
Weight with packaging	580 g

GENERAL INFORMATION

Control type	Facial recognition terminal
--------------	------------------------------------

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

Main processor	Linux
----------------	--------------

