

**HIKVISION**  
accessories



## Controller for 8 (4 doors) readers DS-K2604T-MAINBOARD

### INPUTS/OUTPUTS

|                 |             |
|-----------------|-------------|
| Wiegand         | 4           |
| Alarm input     | 4           |
| RS485           | 8           |
| Door sensor     | 4           |
| Botón de salida | 4           |
| Blocking entry  | 4           |
| Alarm output    | 4           |
| Reader          | 8 (4 Doors) |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -20 °C ~ 65 °C |
| Use                   | Indoor         |
| Maximum humidity      | 90%            |

### MATERIAL AND DIMENSIONS

|            |                   |
|------------|-------------------|
| Dimensions | 236 x 185 x 37 mm |
| Net weight | 680 g             |

### CAPACITY

|          |        |
|----------|--------|
| Cards    | 100000 |
| Register | 300000 |

### POWER CONSUMPTION

|                 |      |
|-----------------|------|
| Power mode      | DC   |
| Voltage         | 12V  |
| Consumption (w) | 100W |

### FUNCTIONS

|                 |    |
|-----------------|----|
| Antipassback    | Sí |
| Multi-interlock | Sí |
| Unlock cards    | Sí |

### COMMUNICATION

|                                  |                         |
|----------------------------------|-------------------------|
| Communication mode to the reader | Wiegand 26 / 34 / RS485 |
| PC communication mode            | RJ45 (10 / 100M)        |

### SPECS AND FEATURES

|                   |   |
|-------------------|---|
| Número de Puertas | 4 |
|-------------------|---|

