



**HIKVISION**  
accessories

## IP video intercom for flush mounting

**DS-KD3003-E6**

### INPUTS/OUTPUTS

|                |                     |
|----------------|---------------------|
| Wiegand        | 1                   |
| Alarm input    | 8                   |
| RS485          | 1                   |
| Door sensor    | 2                   |
| Exit button    | 2                   |
| Blocking entry | 2                   |
| Alarm output   | 2                   |
| RJ45           | 1 x 10 / 100 / 1000 |

### CAMERA

|                          |                |
|--------------------------|----------------|
| Resolution               | 2 Mpx          |
| Horizontal viewing angle | 70°            |
| Diagonal angle of view   | 132°           |
| Night vision             | Yes, up to 3 m |
| Video compression        | H.264          |

### MATERIAL AND DIMENSIONS

|                       |                         |
|-----------------------|-------------------------|
| Installation          | Embed                   |
| Dimensions            | 357.3 x 124.3 x 55.3 mm |
| Net weight            | 1050 g                  |
| Weight with packaging | 2200 g                  |

### GENERAL CHARACTERISTICS (VIDEO INTERCOM)

|                   |           |
|-------------------|-----------|
| Tamper            | Si        |
| Screen            | Si        |
| Type of screen    | LCD       |
| Screen resolution | 320 x 480 |

### OPENING

|                  |                          |
|------------------|--------------------------|
| Call elements    | Simple button            |
| Proximity reader | MIFARE cards             |
| Mode             | Card / Password / Remote |

### GENERAL INFORMATION

|            |    |
|------------|----|
| Technology | IP |
|------------|----|

### POWER CONSUMPTION

|                 |        |
|-----------------|--------|
| Power mode      | DC     |
| Voltage         | 12V    |
| Consumption (w) | 10W    |
| Amperage        | 1000mA |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -40 °C ~ 55 °C |
| Degree of protection  | IP65           |
| Use                   | Indoor-outdoor |
| Maximum humidity      | 95%            |

### SYSTEM (RECORDERS)

|                  |                    |
|------------------|--------------------|
| Processor        | Embedded Processor |
| Operating system | Embedded LINUX     |
| RAM              | 512 MB             |
| ROM              | 4096 MB            |

### AUDIO (VIDEO INTERCOM)

|                   |                             |
|-------------------|-----------------------------|
| Sound input       | Omni-directional microphone |
| Sound output      | Built-in speaker            |
| Audio compression | G.711A / G.711U             |

### CAPACITY

|                   |       |
|-------------------|-------|
| Cards             | 10000 |
| Linked IP cameras | 500   |

### NETWORK CHARACTERISTICS (INTERCOM MONITORS)

|                  |                 |
|------------------|-----------------|
| Network protocol | TCP / IP / RSTP |
|------------------|-----------------|

