



HIKVISION®

Minidome ip camera of 4 megapixels and fix lens

DS-2CD2543G2-IS

VIDEO (CAMERAS)

Resolución vídeo	4 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (120 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Automatic / Manual
Privacy mask	Yes
Type of Codex	CBR / VBR
Bit rate	32Kbps ~ 8Mbps
Compression	H.265+ / H.265 / H.264
Main stream	4Mpx / 1080P / 720P (1 ~ 25fps)
Sub stream	720P / 640 x 480 / 640 x 360 (1 ~ 25fps)
Sub stream 2	1080P / 720P / 640 x 480 / 640 x 360 (1 ~ 10fps)
Anti flap	Yes
Mirror	On / Off

VIDEO ANALYSIS

Tipo de detección	Analytical with human/vehicle classification in line/area crossing
Funciones IA	Detección facial
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Motion detection	Yes
Video Tamper	Sí
Classification Human / vehicle	Sí

IMAGE

Sensor	CMOS ®
--------	---------------

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, type S y G
Maximum number of users	Up to 32 users
Password protection	Yes
Web browser	Explorer / Chrome / Firefox
Management software	iVMS-4200 / Hik-Connect / Hik-Central
Mobile devices	Android / IOS (Apple)
Live view	Up to 6 channels
IP address filter	Yes

AUDIO(CAMERAS)

Built in microphone	Yes
Audio input	1 Input
Audio compression	G.711 / G.722.1 / G.726 / AAC / MP2L2 / MP3 / PCM
Noise filter	SI
Sampling frequency	8 kHz 16 kHz 32 kHz 44.1 kHz 48 kHz
Bit rate	64 Kbps (G.711) / 16 Kbps (G.722.1 / G.726) / 16 ~ 64 Kbps (AAC) / 32 ~ 192 Kbps (MP2L2) / 8 ~ 320 Kbps (MP3)
Audio output	1

LENS

Lens Type	Fix
Focal distance	2.8 mm
Maximum diaphragm opening	F/1.6
Angle of View	104°
Minimum focus distance	600mm
Filtro IR	Sí

NIGHT VISION

Night vision distance	30 m
Tipo de visión nocturna	IR
IR ON/Off	Automatic / Manual
EXIR	Yes

technical datasheet

Resolución sensor	2688 x 1520
Sensor Size	1/3"
Electronic shutter speed	1/3 ~ 1/1000000s
Minimum lighting	0.005Lux
Ratio S / N	Más de 52dB

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	5.5W
Amperage	450mA
PoE power	Yes
Type PoE	PoE 802.3af

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Anti vandal	IK08
Use	Indoor-outdoor
Maximum humidity	95%

SPECS AND FEATURES

Technology	IP
Type of camera	Minidome
Serie	Acusense

AXES

Motion	3-Axis
--------	---------------

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
-------	---------------------------

Wavelength	850 nm
------------	---------------

DISTANCE DORI

Detect	64 m
Observe	18 m
Recognize	9 m
Identify	4 m

MATERIAL AND DIMENSIONS

Dimensions	57.4 x 110 (Ø) mm
Material	Aluminum and plastic
Net weight	380 g
Weight with packaging	620 g

STORAGE

MicroSD-Card	Hasta 512Gb
Storage Systems	NAS / FTP / Micro SD
ANR (Redundant Recording in SD)	Yes

SYSTEM (CAMERAS)

Reset button	Yes
--------------	------------

