

## MOVOK

Bullet ip camera of 5 megapixels and optical zoom lens



VK-IPC-B352-ZAS-TI

### VIDEO (CAMERAS)

Resolución vídeo	<b>5 Megapixels</b>
BLC	<b>Yes</b>
HLC	<b>Yes</b>
3D-NR	<b>Yes</b>
AGC	<b>Yes</b>
AWB	<b>Yes</b>
WDR	<b>WDR (120 dB)</b>
Images per second	<b>25fps</b>
Video output	<b>RJ45</b>
Day / night mode	<b>Colour</b>
Privacy mask	<b>Up to 4 zones</b>
Type of Codex	<b>CBR / VBR</b>
Bit rate	<b>3Kbps ~ 20480Kbps</b>
Compression	<b>H.265 / H.264</b>
Main stream	<b>5Mpx (1 ~ 25fps)</b>
Sub stream	<b>D1 (1 ~ 25fps)</b>
Sub stream 2	<b>720P (1 ~ 25fps)</b>
Mirror	<b>On / Off</b>

### DISTANCE DORI

Detect (Open lens)	<b>67 m</b>
Detect (Closed Lens)	<b>235 m</b>
Observe (Open lens)	<b>27 m</b>
Observe (Closed lens)	<b>95 m</b>
Recognize (Open lens)	<b>13 m</b>
Recognize (Closed lens)	<b>48 m</b>
Identify (Open lens)	<b>7 m</b>
Identify (Closed lens)	<b>24 m</b>

### IMAGE

Sensor	<b>CMOS ®</b>
Resolución sensor	<b>2880 x 1620</b>
Sensor Size	<b>1/2.7'</b>
Electronic shutter speed	<b>1/3 ~ 1/100000s</b>
Minimum lighting	<b>0.001Lux</b>

### VIDEO ANALYSIS

Tipo de detección	<b>Analítica con clasificación humano/vehículo/vehículo no motorizado en cruce de línea/área</b>
Funciones IA	<b>Conteo de personas, mapa de calor, detección facial</b>
Crossing line	<b>Yes</b>
Intrusion	<b>Yes</b>
Face detection	<b>Yes</b>
Motion detection	<b>Yes (4 areas)</b>
Heatmap	<b>Yes</b>
People counting	<b>Yes</b>
Classification Human / vehicle	<b>Sí</b>
SMD	<b>Yes</b>

### NETWORK FEATURES

IP connection	<b>1 RJ45 (10M / 100M)</b>
ONVIF	<b>Yes, G type</b>
Maximum number of users	<b>20 users</b>
Web browser	<b>Explorer / Chrome / Firefox</b>
Management software	<b>Smart PSS / ConfigTool (ambos en red local)</b>
Mobile devices	<b>Android / IOS (Apple)</b>
Network disconnection	<b>Yes</b>
Conflict of IP addresses	<b>Yes</b>

### NIGHT VISION

Night vision distance	<b>50 m</b>
Type of night vision	<b>Dual light (IR+Luz blanca)</b>
IR ON/Off	<b>Automatic / Manual</b>
White light distance	<b>50 m</b>
White light	<b>Sí</b>
Smart Dual Illumination	<b>Yes (switches from IR to colour with human detection)</b>

### MATERIAL AND DIMENSIONS

# technical datasheet

Ratio S / N **More than 56dB**

## POWER CONSUMPTION

Power mode **DC**

Voltage **12V**

Consumption (w) **6.5W**

Amperage **550mA**

PoE power **Yes**

Type PoE **PoE 802.3af**

## LENS

Lens Type **Optical zoom**

Focal distance **2.7 mm ~ 13.5 mm**

Maximum diaphragm opening **F/1.6**

Angle of View **99° ~ 28°**

## SPECS AND FEATURES

Serie **Serie 3**

Technology **IP**

Type of camera **Bullet**

## STORAGE

MicroSD-Card **Up to 256Gb**

Storage Systems **FTP / Micro SD**

Storage anomaly **Yes**

Dimensions **244 x 77 x 76 mm**

Material **Metal**

Net weight **830 g**

Weight with packaging **1000 g**

Color **White**

## AMBIENT

Operating temperature **-30 °C ~ 60 °C**

Degree of protection **IP67**

Use **Indoor-outdoor**

Maximum humidity **95%**

## AUDIO(CAMERAS)

Built in microphone **Yes**

Built in speaker **Yes**

Audio compression **G.711A / G.711U / G.726 / G.726ASF**

## TIOC

Siren **Yes**

Light **blue/ red Light**

## AXES

Motion **3-Axis**

