

MOVOK

Panoramic ip camera of 8 megapíxeles and fix lens

VK-IPC-B582-180AS-TI



VIDEO (CAMERAS)

Video Resolution	8 Megapixels
BLC	Yes
HLC	Yes
3D-NR	Yes
AGC	Yes
AWB	Yes
WDR	WDR (140 dB)
Images per second	25fps
Video output	RJ45
Day / night mode	Colour
Type of Codex	CBR / VBR
Bit rate	3Kbps ~ 16384Kbps
Compression	H.265 / H.264
Main stream	5120 x 1520 (25fps)
Sub stream	2048 x 576 (25fps)
Sub stream 2	2048 x 576 (25fps)
Mirror	On / Off

VIDEO ANALYSIS

Detection type	Analytics with human/vehicle/non-motorized vehicle classification in line/area crossing
AI Functions	People counting, heat map, facial detection with metadata
Crossing line	Yes
Intrusion	Yes
Face detection	Yes
Motion detection	Yes (4 areas)
Abandoned object	Yes
Missing object	Yes
Heatmap	Yes
People counting	Yes
Loitering detection	Yes

NETWORK FEATURES

IP connection	1 RJ45 (10M / 100M)
ONVIF	Yes, G type
Maximum number of users	16
Web browser	Explorer / Chrome / Firefox
Management software	MOVOK (CMS)
Mobile devices	Android / IOS (Apple)
Network disconnection	Yes
Conflict of IP addresses	Yes

IMAGE

Sensor	CMOS ®
Sensor resolution	5120 x 1520
Sensor Size	2 x 1/1.8'
Electronic shutter speed	1/3 ~ 1/100000s
Minimum lighting	Color: 0.007Lux / B/W: 0.0004Lux
Ratio S / N	More than 56dB

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	14W
Amperage	1170mA
PoE power	Yes
Type PoE	PoE 802.3af

MATERIAL AND DIMENSIONS

Dimensions	237 x 110 x 74 mm
Material	Metal
Net weight	760 g
Weight with packaging	920 g
Color	White

METADATA

Face	Yes
Vehicle	Yes

technical datasheet

Classification	
Human / vehicle	Yes
Detección de parking	Yes
SMD	Yes

NIGHT VISION

Night vision distance	40 m
Type of night vision	Dual light (IR+Luz blanca)
IR ON/Off	Automatic / Manual
White light	Sí
White light distance	40 m
Smart Dual Illumination	Yes (switches from IR to colour with human detection)

AUDIO(CAMERAS)

Built in microphone	Yes
Audio input	1 Input
Built in speaker	Yes
Audio compression	G.711A / G.711U / G.726 / G.726ASF
Audio output	1

AMBIENT

Operating temperature	-30 °C ~ 60 °C
Degree of protection	IP67
Use	Indoor-outdoor
Maximum humidity	95%

DISTANCE DORI

Detect	65 m
Observe	26 m
Recognize	13 m
Identify	7 m

STORAGE

MicroSD-Card	Up to 256Gb
Storage Systems	FTP / Micro SD
Storage anomaly	Yes

AXES

Motion	3-Axis
--------	---------------

Human body	Yes
No motorized vehicle	Yes
Search AI (artificial intelligence)	Allows metadata search

LENS

Lens Type	Fix
Focal distance	3.6 mm
Maximum diaphragm opening	F/1.6
Angle of View	180°

GENERAL INFORMATION

Serie	Serie 5
Technology	IP
Type of camera	Panoramic

INPUTS/OUTPUTS (CAMERAS)

Alarm	1 Input / 1 Output
RS485	1 Input

TIOC

Siren	Yes
Light	blue/ red Light

