# technical datasheet





Wireless panel HUB2-4G-DC6V-W

# **ADDITIONAL FEATURES**

Mobile app	Ajax Security System
SMS notification	Sí
Call notification	Sí
Notificación Push	Sí
Maximum number of connected IP cameras	25
Mobile devices	iOS 9.1 or later / Android 4.1 or later
SIM card number	2
LED indicators	Yes
POWER CONSUMPTION	
Power mode	DC
Voltage	4.2V ~ 10V

DC
4.2V ~ 10V

Built in battery	Not
Battery life	± 16 hours

Input current	2200mA @4.2V DC / 500mA @16V DC
---------------	---------------------------------

1500mA Output current

#### **VIA RADIO**

Battery model

Frequency	868mHz
Transmission distance	Up to 2000 m (without obstacles)
Maximum power RF	Class 4 (2W) / 850/900Mhz , Class 2 (1W) / 1800/1900MHz

#### **CERTIFICATION**

Grade	2
Normative	EN50131

## **GENERAL INFORMATION**

Type of Central Wireless

#### SABOTAGE

Box tamper Sí

#### COMMUNICATION

Ethernet	Yes
2G/3G	Yes
4G	Yes
Communication with CRA	Yes, through contactID and SIA
Protocolo	Jeweller

#### MATERIAL AND DIMENSIONS

Dimensions	163 x 163 x 36 mm
Material	ABS plastic
Net weight	360 g
Color	White

#### **AMBIENT**

Operating temperature	5 °C ~ 40 °C
Use	Indoor

#### **ZONES**

6V DC

Maximum number of rooms	50
Maximum number of devices	100

## PARTITIONS AND MEMORIES

Maximum users 50

# **PROCCESSOR**

**OS Malevich** Operating system

