



## Wireless volumetric double technology detector

### MOTIONCAMOUTDOOR-HIGHMOUNT-PHOD-W

#### SENSOR

|                                  |                          |
|----------------------------------|--------------------------|
| Type of sensor                   | <b>PIR and microwave</b> |
| Double PIR sensor                | <b>Sí</b>                |
| Sensitivity adjustment           | <b>Sí</b>                |
| High sensitivity                 | <b>Sí</b>                |
| Half sensitivity                 | <b>Sí</b>                |
| Low sensitivity                  | <b>Sí</b>                |
| Digital temperature compensation | <b>Yes</b>               |

#### DETECTION

|                      |                                     |
|----------------------|-------------------------------------|
| Detector type        | <b>Wireless</b>                     |
| Installation height  | <b>2 m ~ 4 m</b>                    |
| Angle detection      | <b>90°</b>                          |
| Detection distance   | <b>15 m</b>                         |
| Antimasking          | <b>Yes</b>                          |
| Detection technology | <b>Volumetric double technology</b> |

#### AMBIENT

|                       |                       |
|-----------------------|-----------------------|
| Operating temperature | <b>-25 °C ~ 60 °C</b> |
| Degree of protection  | <b>IP55</b>           |
| Use                   | <b>Outdoor</b>        |
| Maximum humidity      | <b>95%</b>            |

#### TECHNICAL SPECIFICATIONS

|                                 |                                  |
|---------------------------------|----------------------------------|
| LED indicators                  | <b>Yes</b>                       |
| Tamper                          | <b>Yes</b>                       |
| Protection against false alarms | <b>Yes, algorithmic analysis</b> |

#### CERTIFICATION

|           |                |
|-----------|----------------|
| Grade     | <b>2</b>       |
| Normative | <b>EN50131</b> |

#### VERIFICACIÓN FOTOGRÁFICA

|                           |                                                            |
|---------------------------|------------------------------------------------------------|
| Angle of view             | <b>115° horizontal / 84° vertical</b>                      |
| Picture quality           | <b>640 x 480 / 320 x 240</b>                               |
| Reception time of a photo | <b>9 s (320 x 240) / 20 s (640 x 480)</b>                  |
| Series images             | <b>1 - 5 images (320 x 240) / 1 - 3 images (640 x 480)</b> |
| Foto bajo demanda (PhOD)  | <b>Yes</b>                                                 |

#### MATERIAL AND DIMENSIONS

|                       |                          |
|-----------------------|--------------------------|
| Dimensions            | <b>234 x 137 x 98 mm</b> |
| Net weight            | <b>620 g</b>             |
| Weight with packaging | <b>1300 g</b>            |
| Support included      | <b>Yes</b>               |

#### VIA RADIO

|                       |                                         |
|-----------------------|-----------------------------------------|
| Frequency             | <b>868.0 MHz ~ 868.6 MHz</b>            |
| Transmission distance | <b>Up to 1700 m (without obstacles)</b> |
| Protocol              | <b>Jeweller / Wings</b>                 |

#### POWER CONSUMPTION

|                  |                     |
|------------------|---------------------|
| Battery model    | <b>6 x CR123A</b>   |
| Battery duration | <b>Up to 3 años</b> |

#### GENERAL INFORMATION

|               |                                                                    |
|---------------|--------------------------------------------------------------------|
| Compatibility | <b>Hub 2 (2G / 4G) / Hub 2 Plus / Hub Hybrid (2G / 4G) / Rex 2</b> |
|---------------|--------------------------------------------------------------------|

