



**HIKVISION**  
intrusion

## 96-zone wireless panel

**DS-PWA96-M-WE**

### POWER CONSUMPTION

|                 |             |
|-----------------|-------------|
| Power mode      | AC          |
| Voltage         | 100V ~ 240V |
| Amperage        | 200mA       |
| Battery life    | ± 12 hours  |
| Battery support | Included    |
| Battery model   | 4520mAh     |

### COMMUNICATION

|           |                  |
|-----------|------------------|
| Wi-Fi     | Sí               |
| RS232     | 1                |
| TCP/IP    | Sí               |
| Protocolo | SIA - Contact ID |
| 3G        | Sí               |
| 4G        | Yes              |

### MATERIAL AND DIMENSIONS

|                       |                     |
|-----------------------|---------------------|
| Dimensions            | 170 x 170 x 38.6 mm |
| Material              | Plastic             |
| Net weight            | 550 g               |
| Weight with packaging | 900 g               |

### VIA RADIO

|                                             |        |
|---------------------------------------------|--------|
| Frequency                                   | 868mHz |
| Maximum number of transmitters per repeater | 6      |
| Maximum number of repeaters                 | 4      |

### CERTIFICATION

|                     |    |
|---------------------|----|
| Grade               | 2  |
| Environmental class | II |

### SABOTAGE

|            |    |
|------------|----|
| Box tamper | Sí |
|------------|----|

### ADDITIONAL FEATURES

|                   |     |
|-------------------|-----|
| Voice report      | Sí  |
| SMS notification  | Sí  |
| Call notification | Sí  |
| SIM card number   | 2   |
| LED indicators    | Yes |

### ZONES

|                           |                             |
|---------------------------|-----------------------------|
| Maximum number of zones   | 96                          |
| Keyboards                 | 8                           |
| Sirens                    | 6 (3 internal / 3 external) |
| PIR detectors with camera | 48                          |

### GENERAL INFORMATION

|                 |          |
|-----------------|----------|
| Serie           | AXPRO    |
| Type of Central | Wireless |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 55 °C |
| Use                   | Indoor         |

### PARTITIONS AND MEMORIES

|                     |      |
|---------------------|------|
| User codes          | 46   |
| Registration events | 5000 |

