



HIKVISION
intrusion

Wireless volumetric detector DS-PDP15P-EG2-WE

DETECTION

| | |
|---|------------------------|
| Detector type | Wireless |
| Installation height | 2 m ~ 4 m |
| Angle detection | 90° |
| Detection distance | 15 m |
| Detection speed | 0,3 m/s ~ 2 m/s |
| Detection zones | 84 |
| Pets immunity | Up to 30 Kg |
| PIR detection advance at ground level (PIR Creep) | Sí |

POWER CONSUMPTION

| | |
|------------------|---------------------|
| Power mode | Battery |
| Built in battery | Yes |
| Battery model | CR123A / 3V |
| Battery duration | Up to 5 años |

TECHNICAL SPECIFICATIONS

| | |
|----------------|-------------------------|
| Compatibility | Hikvision panels |
| LED indicators | Yes |
| LED colors | Blue |
| Tamper | Yes |

CERTIFICATION

| | |
|---------------------|-----------|
| Grade | 2 |
| Environmental class | II |

GENERAL INFORMATION

| | |
|-------|--------------|
| Serie | AXPRO |
|-------|--------------|

MATERIAL AND DIMENSIONS

| | |
|-----------------------|-----------------------------|
| Installation | Wall / ceiling |
| Dimensions | 103 x 65.5 x 48.5 mm |
| Net weight | 100 g |
| Weight with packaging | 170 g |

AMBIENT

| | |
|-----------------------|-----------------------|
| Operating temperature | -10 °C ~ 55 °C |
| Use | Indoor |
| Maximum humidity | 90% |

SENSOR

| | |
|----------------------------------|------------|
| Type of sensor | PIR |
| Sensitivity adjustment | Sí |
| Digital temperature compensation | Yes |

VIA RADIO

| | |
|-----------------------|---|
| Frequency | 868mHz |
| Transmission distance | Up to 1600 m (without obstacles) |