technical datasheet



HIKVISION° intrusion

Wireless volumetric detector DS-PDP15P-EG2-WE

DETECTION

Detector type	Wireless
Installation height	2 m ~ 4 m
Angle detection	90°
Detection distance	15 m
Detection speed	0,3 m/s ~ 2 m/s
Detection zones	84
Pets immunity	Up to 30 Kg
PIR detection advance at ground level (PIR Creep)	Sí

POWER CONSUMPTION

Power mode	Battery
Built in battery	Yes
Battery model	CR123A / 3V
Battery duration	Up to 5 años

TECHNICAL SPECIFICATIONS

Compatibility	Hikvision panels
LED indicators	Yes
LED colors	Blue
Tamper	Yes

CERTIFICATION

Grade	2
Environmental class	Ш

GENERAL INFORMATION

Serie		AXPRO)

MATERIAL AND DIMENSIONS

Installation	Wall / ceiling
Dimensions	103 x 65.5 x 48.5 mm
Net weight	100 g
Weight with packaging	170 g
AMBIENT	
Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%
SENSOR	
Type of sensor	PIR
Sensitivity adjustment	Sí
Digital temperature compensation	on Yes
VIA PADIO	

Frequency	868mHz
Transmission	Up to 1600 m (without
distance	obstacles)