



## AJAX

### Seismic detector

### SEISMOPROTECT-FIBRA-G3-B

#### DETECTION

|                            |                                            |
|----------------------------|--------------------------------------------|
| Detection distance         | 2 m radius (steel) / 4 m radius (concrete) |
| Temperature for alarm jump | 70°                                        |
| Vibration sensitivity      | 3 levels                                   |
| Ignore first vibration     | Sí, opcional                               |
| Detection technology       | Seismic                                    |
| Detección de inclinación   | Yes, from 5° to 25°                        |
| Detección de choque        | Yes                                        |

#### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -25 °C ~ 70 °C |
| Degree of protection  | IP43           |
| Anti vandal           | IK04           |
| Use                   | Indoor         |
| Maximum humidity      | 95%            |

#### POWER CONSUMPTION

|                     |                         |
|---------------------|-------------------------|
| Power mode          | DC (via Hub Hybrid BUS) |
| Voltage             | 24V                     |
| Standby consumption | 0.3mA                   |
| Maximum consumption | 12mA                    |

#### SENSOR

|                                  |                |
|----------------------------------|----------------|
| Type of sensor                   | Piezoeléctrico |
| Digital temperature compensation | Sí             |
| Accelerometer                    | Yes            |

#### MATERIAL AND DIMENSIONS

|                       |                            |
|-----------------------|----------------------------|
| Dimensions            | 88 x 88 x 20 mm            |
| Material              | Aluminum and polycarbonate |
| Net weight            | 380 g                      |
| Weight with packaging | 700 g                      |
| Color                 | Black                      |

#### ESPECIFICACIONES TÉCNICAS

|                                 |                           |
|---------------------------------|---------------------------|
| Tamper                          | Dual                      |
| Connection type                 | 4 wires                   |
| Protection against false alarms | Yes, algorithmic analysis |
| Transmission distance           | Up to 2000 m              |

#### GENERAL INFORMATION

|               |                     |
|---------------|---------------------|
| Technology    | Wired               |
| Compatibility | Hub Hybrid (2G /4G) |

#### CERTIFICATION

|           |         |
|-----------|---------|
| Grade     | 3       |
| Normative | EN50131 |

