




5 ports cloud switch with 4 PoE ports

DS-3E1105P-EI/M



REMOTE MANAGEMENT

Software	Hik Partner Pro
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

POWER CONSUMPTION

Power mode	DC
Voltage	54V
Consumption (w)	50W
Amperage	920mA
Standby consumption	5W
Maximum consumption per port (PoE)	30W
Total maximum consumption (PoE)	45W

ETHERNET PORTS

POE ports	4
Uplink ports	1
POE Ports Speed	10 / 100
Uplink ports speed	10 / 100
Number of Ethernet ports	5
Puertos PoE prioritarios	2 (priorizados en caso de congestión)

NET STANDARD

IEEE802,3af	Yes
IEEE802,3at	Yes

CHARACTERISTICS (SWITCH)

Data rate supported	1.2 Gbps
Packet redirection speed	0.89 Mpps
VLAN	802.1Q
Maximum transmission distance	300 m
Buffer Memory	768K
PoE Watchdog	Yes
Spanning Tree	Yes, STP / RSTP

MATERIAL AND DIMENSIONS

Installation	Desk / wall
Dimensions	121.1 x 83.1 x 27.6 mm
Material	Metal
Net weight	260 g
Weight with packaging	750 g

AMBIENT

Operating temperature	0 °C ~ 40 °C
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

SYSTEM (SWITCH)

MAC address table	2K
-------------------	-----------

