



HIKVISION
intrusion

Wired keyboard

DS-PK501LTM-HWE

CHARACTERISTICS (KEYBORDS)

Connection	Wired
Screen	Sí
Screen type	LCD
LED keyboard	Sí
Compatibility	Hikvision panels
Panic alarms	3
Tamper	Sí, cubierta y pared
Transmission distance	900 m
Frequency	868.0 ~ 868.6 MHz
Zonas	2

POWER CONSUMPTION

Power mode	DC (via BUS)
Voltage	12V
Amperage	200mA
Standby consumption	40mA
Relay output type	DC
Relay voltage output	30V
Relay Amperage output	1000mA

MATERIAL AND DIMENSIONS

Dimensions	175 x 110 x 27 mm
Net weight	300 g
Weight with packaging	440 g

ADDITIONAL FEATURES

Keyfob	64
Tags	3 included

FUNCTIONS (KEYBOARDS)

Armed function	Sí
Unarmed function	Sí
Teclas funcionales	8
Lector de proximidad	Sí, MIFARE

AMBIENT

Operating temperature	-10 °C ~ 50 °C
Use	Indoor
Maximum humidity	90%

GENERAL INFORMATION

Serie	AXPRO
Compatibility	Hikvision panels

CERTIFICATION

Grade	2
Environmental class	II

