



HIKVISION
accessories

12 ports cloud switch with 8 PoE ports

DS-3T1512HP-SI-8P4F

CHARACTERISTICS (SWITCH)

Data rate supported	56 Gbps
Packet redirection speed	41.7 Mpps
VLAN	802.1Q
DHCP	Si
Maximum transmission distance	300 m
Buffer Memory	4.1 Mb
Mirror port	Si
PoE Watchdog	Yes
Spanning Tree	Yes, STP / RSTP / ERPS
QoS	Yes
Port Aggregation	LACP / Static aggregation (max. 8 groups)
Industrial	Yes

REMOTE MANAGEMENT

P2P	Yes
Software	Hik Partner Pro
Reset switch	Yes
PoE port reset	Yes
Extended mode activation	Yes, independently per port
Port speed modification	Yes
Actual power consumption	Yes, total and per port
History of peak consumption	Yes (up to 7 days)
Real-time traffic information	Yes, by port
Connected device information	Yes, for Hikvision equipment (IP, model, and SN)
Automatic topology diagram	Yes, for connected Hikvision devices

MATERIAL AND DIMENSIONS

Installation	DIN rail / desktop
Dimensions	155 x 130 x 46 mm
Material	Metal
Net weight	840 g

POWER CONSUMPTION

Power mode	DC
Voltage	48V ~ 57V
Consumption (w)	307W
Amperage	7500mA
Standby consumption	7W
Maximum consumption per port (PoE)	Ports 1-4: 90W / Ports 5-8: 30W
Total maximum consumption (PoE)	300W
Power supply included	No

AMBIENT

Operating temperature	-40 °C ~ 75 °C
Degree of protection	IP40
Use	Indoor
Maximum humidity	95%
Lightning protection	6KV

ETHERNET PORTS

POE ports	8
Fiber port	4 x 1000
POE Ports Speed	10 / 100 / 1000
Number of Ethernet ports	12

NET STANDARD

IEEE802.3af	Yes
IEEE802.3at	Yes
IEEE802.3bt	Sí, puertos 1 ~ 4

Weight with packaging

1160 g

SYSTEM (SWITCH)

MAC address table

16K

